

**NEW**



**RACO**<sup>®</sup>

A Division of Hubbell Incorporated (Delaware)

# Conduit Clamps

**Parallel Type**



**Edge Type**



**Right Angle Type**



## Applications


Designed to secure rigid metal conduit, IMC or EMT across, parallel or perpendicular to channel, beam and angle supports

## Features

- Three styles meet every installation need
- Heavy duty U-bolts, hex bolts and hex nuts
- Capable of supporting heavy loads
- Hot dipped galvanized malleable iron construction provides excellent weatherability and corrosion protection
- Perfect for commercial construction applications
- UL listed for your safety and peace of mind

*Specifications on reverse side*






## Parallel Type Clamps

Cat. No.	Trade Size	Carton Qty.	A	B	Wt. lbs./100	Max. Ld. Sup. @10' Spacing Intervals	Ctn. 1 2 of 5
2322PC	1/2"	50	2-7/8"	1-7/16"	53.8	50 lbs	50050169986108
2323PC	3/4"	50	3-1/16"	1-11/16"	59.7	50 lbs	50050169986115
2324PC	1"	50	3-1/4"	2"	62.4	60 lbs	50050169986122
2325PC	1-1/4"	25	3-5/8"	2-1/8"	80.6	75 lbs	50050169986139
2326PC	1-1/2"	25	3-7/8"	2-3/16"	86.5	80 lbs	50050169986146
2328PC	2"	25	4-5/8"	2-7/8"	99.6	100 lbs	50050169986153
2330PC	2-1/2"	25	5-1/4"	3-1/4"	130.4	125-160 lbs. @10'-16'	50050169986160
2332PC	3"	5	5-7/8"	3-7/8"	161.2	165 lbs. @10'-20'	50050169986177
2334PC*	3-1/2"	5	6-5/16"	4-5/16"	190.4	200-375 lbs. @10'-20'	50050169986184
2336PC*	4"	5	6-13/16"	4-13/16"	210	230-470 lbs. @10'-20'	50050169986191

\*UL Listing Pending.


Country of Origin, China

## Edge Type Clamps



Cat. No.	Trade Size	Carton Qty.	A	B	Wt. lbs./100	Max. Ld. Sup. @10' Spacing Intervals	Ctn. 1 2 of 5
2302EC	1/2"	25	2-13/16"	2-1/8"	77.3	50 lbs	50050169986023
2303EC	3/4"	25	2-15/16"	2-3/8"	80.6	50 lbs	50050169986030
2304EC	1"	25	3-1/16"	2-5/8"	88.9	60 lbs	50050169986047
2305EC	1-1/4"	25	3-1/16"	3-1/16"	100.6	75 lbs	50050169986054
2306EC	1-1/2"	25	3-15/16"	3-1/4"	112.8	80 lbs	50050169986061
2308EC	2"	25	4-1/2"	4-1/16"	175.2	100 lbs	50050169986078
2310EC	2-1/2"	25	5-1/8"	4-5/8"	206.9	125-160 lbs. @10'-16'	50050169986085
2312EC	3"	5	5-3/4"	5-1/4"	246	165 lbs. @10'-20'	50050169986092

Country of Origin, China



## Right Angle Type Clamps

Cat. No.	Trade Size	Ctn. Qty.	A	B	C	D	E	Wt. lbs./100	Max. Ld. Sup. @10' Spacing Intervals	Ctn. 1 2 of 5
2352RC	1/2"	50	1"	1-1/4"	2-1/2"	1-13/16"	2-1/16"	34.9	50 lbs	50050169986207
2353RC	3/4"	50	1-1/8"	1-3/8"	2-13/16"	1-13/16"	2-1/4"	38.6	50 lbs	50050169986214
2354RC	1"	50	1-3/8"	1-5/8"	3-1/16"	1-13/16"	2-9/16"	43.8	60 lbs	50050169986221
2355RC	1-1/4"	25	1-3/4"	2"	3-3/16"	1-13/16"	2-7/8"	48.5	75 lbs	50050169986238
2356RC	1-1/2"	25	2"	2-3/8"	3-1/2"	1-13/16"	3-1/4"	54.8	80 lbs	50050169986245
2358RC	2"	25	2-1/2"	2-1/2"	4-1/2"	2-5/8"	4-1/16"	92.6	100 lbs	50050169986252
2360RC	2-1/2"	10	3"	3-1/4"	4-7/8"	2-5/8"	4-1/2"	106.5	125-160 lbs. @10'-16'	50050169986269
2362RC	3"	5	3-5/8"	3-7/8"	5-3/8"	2-5/8"	5-1/8"	126.4	165 lbs. @10'-20'	50050169986276
2364RC	3-1/2"	5	4-1/16"	4-9/16"	5-7/8"	2-5/8"	5-5/8"	136	200-375 lbs. @10'-20'	50050169986283
2366RC	4"	5	4-11/16"	5-1/16"	6-11/16"	2-5/8"	6-1/8"	163.4	230-470 lbs. @10'-20'	50050169986290

Country of Origin, China



**RACO**<sup>®</sup>

A Division of Hubbell Incorporated (Delaware)

Distributed By:

3902 West Sample St. P.O. Box 4002  
 South Bend, IN 46619-4002  
 TEL: 574-234-7151 FAX: 574-234-0625  
 www.hubbell-raco.com